

AirNugz 800 / Filtered Air Purifier

Air Purification and Odor Neutralization for Small Greenhouses Cross Contamination Prevention AirNugz Filtration 800 for Odorless Space.



Virtually indestructible:

The heavy duty roto molded box is leak proof and virtually indestructible.

Standard filters:

16" x 16" x 3" Fill-Pure DUAC Honeycomb Filter (5 lbs of dual activated media)
16" x 16" x 1" Fill-Pure Tri-Tek PreFilter
16" x 16" x 1/2" Fill-Pure MERV Filter

Low power requirements:

Drawing only 3 amps, the AirNugz 800 can be daisy chained up to three units. The built in GFCI outlets allow for safe and effective operation. The AirNugz straight through design makes it ideal for virtually any application.

• Utilizes standard "Lay flat" or flex ducting:

10" intake to 12" exhaust vacuum ports allows for maximum airflow with little restriction. Ducting can be used to exhaust filtered air outside or to bring in fresh air from outside.

• Efficiency:

The AirNugz 800 is powerful yet portable filtration system engineered for critical air filtration and odor neutralization. By combining true DUAC filtration (Dual Activation) with our "Duac-Pure" three stage odor controlling filter, the Airganics AirNugz is the most efficient filtration system in its class.

Versatility:

The AirNugz 800 is used in a variety of applications ranging from odor and fume removal, air purifying, food processing and laboratory cross contamination prevention and containment of airborne pathogen for medical and hospital uses.





AirNugz 800 / Filtered Air Purifier



Features

- Low power requirements
- Variable speed adjustment, delivers 200-800 CFM
- The tri-gasket filter sealing flange assures leak proof operation
- Three stage filtration through DUAC Honeycomb Filter, Tri Tek and MERV dust filters
- Easy filter change with the guick release intake door
- Integrated nesting allows for the stacking of up to 3 machines
- Built-in GFCI outlet allows you to connect multiple equipment up to 15 amps
- 10 to 12 inch vacuum ports allows for maximum airflow
- Available in a variety of power sources (115V-230V, 50/60 Hz

Benefits

- No installation necessary. Turnkey system. Plug and filter!!!
- · Removes any organically generated odor via the DUAC Honeycomb Filter
- Exhaust clean odorless air after filtration
- Increase airflow in greenhouses
- Renew fresh clean air supply
- Portable and easily movable and transportable
- · Variable speed rheostat permits user to adjust the air exchange rate
- Prevents cross contamination by odor
- Restore outside air quality inside any close space
- Air purification for food processing facilities grow area and laboratories

Ai	r	Ex	ch	an	ae	Cal	cula	atio	n F	orm	nula	For	Your	Sp	ace
/AA		141.			H		I- 4 \	- 6 4			/ D:	- 1/1	OF		4

(Width x length x height) of the room / BioKlean CFM output = minutes for complete air exchange (x ____x ___) / ____ = ___ minutes for comp 60/ # of complete air exchange = # of air exchange per hour _ minutes for complete air exchange

air exchange per hour

 $(CFM \times 60)/(W \times L \times H) = Air exchange per Hour$

N	/lodel	Part No.	Weight	Dimensions	Air Volume	Power	Filter	
AirN	Nugz 800	AN800	45 lbs 21 kg	22" x 22" x 21" 55 cm x 55 cm x 52 cm	Variable 200-800 CFM 340-1200 m ³ /hr	115 Volt 3 amp, 60 Hz	DUAC Honeycomb Tritek and MERV	
AirN	lugz 800	AN805	45 lbs 21 kg	22" x 22" x 21" 55 cm x 55 cm x 52 cm	Variable 200-800 CFM 340-1200 m ³ /hr	230 Volt 1.7 amp, 50/60 Hz	DUAC Honeycomb Tritek and MERV	